

# Auto 500 Series

VFFS Machines with Proven Technology



## Auto 500 Specifications

	Standard		Jumbo	
	Min	Max	Min	Max
Pouch Width	70mm	230mm	100mm	350mm
Pouch Height	75mm	350mm	100mm	500mm
Film Width	160mm	500mm	220mm	730mm
Output	up to 3000 pouch per hour or more achievable based on product density, shape, fill weight, film quality and operator skills			
Pouch Type	Pillow Type Centre Sealed			
Approximate Dimension				
Bagger Width	800 mm		1100 mm	
Bagger Length	1350 mm		1500 mm	
Bagger Height	1650 mm		2000 mm	
Approximate Bagger Weight	700 Kg		1200 Kg	
Packaging Film	All Heat Sealable Laminate, Co-extruded LDPE-LLDPE Films			
Power- Rating - Bagger	3 Phase, 440V AC, 50 Hz, Stabilised			
Compressed Air Consumption (FAD)	250 LPM		300 LPM	
Pressure	6.0 Kg/Cm2		7.0 Kg/Cm2	



Works: Plot No: 6/2/22-23, GIDC Estate,  
Por-Ramangamdi-391243, Dist. Vadodara, Gujarat (India).

Mobile : +91-95744 91114/ 9574491115

email : info@prolificpackaging.com

nikhil@prolificpackaging.com

www.prolificpackaging.com

Note: Specifications given above are subject to change without prior notice.

Automatic form fill seal packing machine is suitable to pack range of products such as powders, grains, pulses, hardware etc. using Heat Sealable Laminate Film. Machine is rigid, versatile and engineered for reliability and enhance operational efficiency in addition, it has several exclusive feature which offer additional advantages.

Packaging film roll is mounted on roll mounting assembly and it travels towards forming collar through film unwinding mechanism. Photocell sensor stops film at an appropriate cutting position. Packaging film forms a tube after forming collar and vertical seal is performed. FILLER is an independent device which feeds product as per desired volume/weight. Product is loaded such that level is maintained in the hopper. Post product dump into the formed pouch, horizontal seal & cutting take place to produce finished pouch. The speed of the machine is up to 3000 packs per hour and more depending on product, desired fill weight, packaging film type, quality & operator skills.



Works: Plot No: 6/2/22-23, GIDC Estate,  
 Por-Ramangamdi-391243, Dist. Vadodara, Gujarat (India).  
 Mobile : +91-95744 91114/ 9574491115  
 email : info@prolificpackaging.com  
 nikhil@prolificpackaging.com  
 www.prolificpackaging.com

## Our Customers



NUTS

ENERGY DRINKS

BESAN / ATTA

SALT



NAMKEEN

SPICES



DETERGENT



PESTICIDE



SEEDS



WALL PUTTY

## Optional Features

	Standard	Jumbo
Servo Controlled Auger	Y	Y
Servo Controlled Film Pulling	Y	Y
Servo Controlled Cross Sealing	Y	Y
Side Gusset Attachment	Y	Y
Nitrogen Flushing Attachment	Y	Y
Strip Perforation Attachment	Y	-
Pin Hole Attachment	Y	Y
Batch Coding Attachment	Y	Y
Handle Punch	-	Y

## Filler Selection

Auger Filler	Cup Filler	Weigh Filler
Spice Powder	Grains / Pulses / Sugar	
Instant Mix Powder	Mung Dal, Chana Dal, Freid Green Peas	
Milk Powder	Crop Seeds / Vegetable Seeds	
Atta, Besan, Maida	Free Flowing Salt	Confectionery
Refined Salt, Crystal Salt	Fasteners	
Pesticide Powder		
Wall Putty / White Cement		